AXTAL ADVANCED XTAL PRODUCTS


Specification	AXQCM598-Cu	Rev.: 3	Date: 2014-06-02

Oscillator type : Quartz Crystal Microbalance Element


Electrodes Maxtek Style

Parameter	min.	typ.	max.	Unit	Condition
Nominal frequency		6.000		MHz	
Adjustment frequency		5.983		MHz	
Crystal cut		AT			
Overtone		1			
Adjustment tolerance	-7		+7	kHz	@ 25°C
Frequency stability					
Over operating temperature range	-50		+50	ppm	
Resonance resistance R_r			60	Ω	
Motional capacitance C_1				fF	
Shunt capacitance C_0			7	pF	
Drive level		100		µW	
Operating temperature range	0		+70	°C	
Storage temperature range	-40		+105	°C	
QCM diameter		13.97 ± 0.03		mm	
Blank surface quality		Fine lapped			
Elextrode diameter Side A		13.0 ± 0.1		mm	Fully plated
Electrode material Side A		Cr-Cu			
Electrode diameter Side B		6.4		mm	See drawing
Electrode material Side B		Cr-Cu			

Side A (Plane)



Side B (Convex)



Ordering Code:

Model (Specification)	Frequency [MHz]
AXQCM598-Cu	5.983

Revision History

Rev.	Drawing	Date [dd.mm.yyyy]	Remarks	Author	Checked
2	D0	16.10.2013		EP	BN
3	D1	02.06.2014	Editorial changes	BN	BN